



# S-100

## SERVICE INFORMATION HATZ Diesel Engine

**Parts List for Routine Service of  
HATZ 3H50 Industrial Diesel Engine (Tier 4 Final)**  
Refer to Engine Manufacturer's Service Manual for Engine Service Details  
(Engine must be serviced every 500 hours of operation or as needed)

Description	Air Burners P/N	Manufacturer's P/N	Service Interval
Air Filter (Main Element H50)	5000-2338	HATZ 50638200	500 Hours
Air Filter (Secondary Element H50)	5000-2339	HATZ 50638300	500 Hours
Oil Filter H50	5000-2340	HATZ 50638800	500 Hours
Oil Separator H50	5000-2341	HATZ 50640500	500 Hours
Fuel Filter H50	5000-2342	HATZ 50638100	500 Hours
Pre-Fuel Filter	5000-2343	HATZ 50638000	500 Hours
Poly-V-Belt (Engine) H50	5000-2344	HATZ 50629401	500 Hours
Fuel/Water Separator Filter	5000-1297	RACOR R20P	As needed
CAT Battery (12V, CCA 800, AH 50)	5000-2050	CAT 8C-3612	2 Years or as needed

Diesel Fuel	Ultra Low Sulfur Fuel Only
Engine Oil	10W40 Diesel Grade - Ultra-Low Sulfur (Most Regions)
Engine Coolant	Low Silicon Anti-Freeze (Green). Shipped with 50/50 Mixture Anti-freeze/water
Bearing Lubricant	NLGI Grade 2
DEF and DPF <sup>*)</sup>	Not required (Engine meets US EPA Tier 4 Final and EU 97/68 Stage 3 B)
Fuel Tank Capacity	Minimum 58 Gallons (220 Liters)
<b>Consult Operating Manual for PTO and engine-to-air fan coupler service and adjustment.</b>	
*) DEF = Diesel Exhaust Fluid      DPF= Diesel Particulate Filter	

**AIR BURNERS, INC.**  
4390 SW Cargo Way • Palm City, FL 34990  
Phone 772-220-7303 • FAX 772-220-7302  
E-mail: info@airburners.com • www.AirBurners.com  
© 2018 Air Burners, Inc.4