

SERVICE INFORMATION

HATZ Diesel Engine

**Parts List for Routine Service of
HATZ 3H50TIC Industrial Diesel Engine (Tier 4 Final)**
Refer to Engine Manufacturer's Service Manual for Engine Service Details
(Engine must be serviced every 500 hours of operation or as needed)

Description	Air Burners P/N	Manufacturer's P/N	Service Interval
Air Filter (Main Element H50)	5000-2338	HATZ 50638200	500 Hours
Air Filter (Secondary Element H50)	5000-2339	HATZ 50638300	500 Hours
Oil Filter H50	5000-2340	HATZ 50638800	500 Hours
Oil Separator H50	5000-2341	HATZ 50640500	500 Hours
Fuel Filter H50	5000-2342	HATZ 50638100	500 Hours
Pre-Fuel Filter	5000-2343	HATZ 50638000	500 Hours
Poly-V-Belt (Engine) H50	5000-2344	HATZ 50629401	500 Hours
Fuel/Water Separator Filter (Optional)	5000-1297	RACOR R20P	As needed
CAT Battery	5000-2050	CAT 8C-3612	2 Years

Diesel Fuel	Ultra Low Sulfur Fuel Only
Engine Oil	10W40 Diesel Grade - Ultra-Low Sulfur (Most Regions)
Engine Coolant	Low Silicon Anti-Freeze (Green). Shipped with 50/50 Mixture Anti-freeze/water
Bearing Lubricant	NLGI Grade 2
DEF and DPF ^{*)}	Not required (Engine meets US EPA Tier 4 Final and EU 97/68 Stage 3 B)
Fuel Tank Capacity	Minimum 58 Gallons (220 Liters)
Consult Operating Manual for PTO and engine-to-air fan coupler service and adjustment.	
*) DEF = Diesel Exhaust Fluid DPF= Diesel Particulate Filter	

AIR BURNERS, INC.
4390 SW Cargo Way • Palm City, FL 34990
Phone 772-220-7303 • FAX 772-220-7302
E-mail: info@airburners.com • www.AirBurners.com
© 2018 Air Burners, Inc.