



T-24 / T-22

BURNBOSSE SERVICE INFORMATION

**Parts List for Routine Service of
Kubota Industrial Diesel Engine Z482-E3**
Refer to Engine Manufacturer's Service Manual for Engine Service Details
(Engine must be serviced first after 50, then every 200 hours of operation)

Description	Air Burners P/N	Manufacturer's P/N	Service Interval
Air Cleaner Element	3060-1022	Kubota 1G659-11222	1 Year or as needed
Oil Filter	3060-1020	Kubota HH150-32430	200 Hours
Fuel Filter	3060-1021	Kubota 70000-43081	400 Hours
V-Belt (Engine)	3060-1023	Kubota 15881-97010	500 Hours
Electrical System Fuse 40A Amp ID: Green, Style: MAXI	5000-0302	NAPA BK7821079	As needed
CAT Battery (12V, CCA 800, AH 50)	5000-2050	CAT 8C-3612	2 Years or as needed

Tire Pressure	110 psi (760 kpa)
Tire Size	ST235/85R16
Rim	16 x 6 (8 Lugs)
Engine Oil	15W40 Diesel Grade
Engine Coolant	Low Silicon Anti-Freeze (Green). Units are shipped from factory with 50-50 mixture green antifreeze/water.
Hydraulic Oil	ISO32 Synthetic Hydraulic oil, factory installed is Amsoil HVH05-EA. (cold weather option is ISO22 synthetic, i.e. Amsoil HVG05EA). Capacity is approximately 2.16 gallons (8.19 liters). Change Hydraulic Oil every 1 to 2 years, depending on environment.
Break-Away Switch	12V Battery - See owner's manual
Fuel Tank Capacity	Minimum 9.9 Gallons (8.2 Liters)

AIR BURNERS, INC.
4390 SW Cargo Way • Palm City, FL 34990
Phone 772-220-7303 • FAX 772-220-7302
E-mail: info@airburners.com • www.AirBurners.com
© 2018 Air Burners, Inc.