

ROLL-OFF FIREBOX SPECIFICATIONS



General: A self-contained, completely assembled above ground Air Curtain Burner (air curtain incinerator or FireBox) with a refractory lined burn-container and steel floor and fittings for cable-hoist trucks in accordance with ANSI Specification Z245.60 for portable applications.

Designed for the high temperature burning of forest slash, agricultural green waste, land clearing debris, storm debris, and other waste streams in compliance with the requirements of US EPA 40CFR60. The FireBox is also used for disaster recovery and Department of Homeland Security contingencies.

Hook-lift and Continuous Chain Roll-off versions also available. Shipped from the factory completely assembled ready for immediate use.

1	Power	Three-cylinder Turbo Diesel Engine approx. 49 HP, HATZ Model 3H50TIC (Requires no DEF) or equivalent engine; Emissions certified US EPA Tier 4 FINAL; Engine mounted PTO	
2	Burn Container (Firebox)	4" (102mm) thick refractory panels filled with proprietary thermal ceramic material; Two full height rear doors; Two ignition holes	
3	Safety Systems	Engine over temperature and overspeed shut down; Loss of cooling fluid shutdown; Loss of oil pressure shutdown; Lockable steel front deck security enclosure	
4	Instrument Panel	MBW electronic engine control with preset throttle settings: key switch, tachometer, hour meter, fuel gauge, oil pressure and water temperature and safety shutdown features	
5	Air Supply	Custom heavy duty fan	
6	Fuel Tank	58 Gallon (220L) minimum fuel tank capacity	
7	Transportation & Set-up	Shipped completely assembled; Ready for immediate use; Lifting pads provided for crane lifting	
8	Options	Ash clean-out rake with standard universal quick disconnect for <i>Skidsteer</i> or <i>Bobcat</i> ; Hook-lift and Continuous Chain Roll-off Versions	
9	Average Through-put	2-4 Tons per Hour (Average – See Note)	
10	Fuel Consumption	Approx. 1.9 gal/hr. (7.2L/hr.)	
11	Weight	35,300 lbs. (16,117kg)	
12	Dimensions	Overall Size L × W × H	Fire Box L × W × H
		23" × 7' 5" × 8' 6" (7m × 2.2m × 2.6m)	16' × 5' × 6' (4.9m × 1.5m × 1.8m)

Note:

Achievable through-put depends on several variables, especially the nature of the waste material, the burn chamber temperature and the loading rate.

All weights and dimensions are approximate and metric conversions are rounded. Specifications are subject to change without notice.

AIR BURNERS, INC.

4390 SW Cargo Way • Palm City, FL 34990

Phone 772-220-7303 • FAX 772-220-7302

E-mail: info@airburners.com • www.AirBurners.com

© 2019 Air Burners, Inc.

Rev. 06.18.2019